

### NOCO BOOST® PLUS® JUMP STARTER



## START DEAD BATTERIES.

#### Cars, Boat, Motorcycles, ATVs, Trucks & More.

UltraSafe, ultra-compact, rugged, and portable lithium-ion jump starter. Features spark-proof technology and reverse polarity protection. Instantly jump starts most single-battery applications, up to 20 times on a single charge. Ideal for a wide range of vehicles including trucks and engines up to 6.0L Gas and 3.0L Diesel.



Safely connect to any 12-volt car battery with our mistake-proof design featuring spark-proof technology and reverse polarity protection.

### JUMP START.

Full power to jump start a vehicle up to 20 times in one charge. Compatible with engines up to 6.0L gas and 3.0L diesel.

#### **USB** CHARGE & RECHARGE.

It's internal battery can be used to recharge any personal mobile devices like smartphones, tablets, or any other USB device, and can be recharged by any powered USB port.

### 100 LUMENS.

The GB40 portable car battery jump starter integrates with a high-output 100 lumen LED flashlight with 7 light modes: low, medium, high, flashing, strobe, and emergency SOS.







# A Fraction Of The Size.



Compact, portable. pocket-sized jump starter that fits perfectly in your glove box.

#### **1 Year+** Holds Charge 4x Longer

The GB40 holds the charge four times longer to extend battery power life and eliminate charge time.

Compared to Leading Traditional Lead Acid Jump Starters



(!)

Error LED. Illuminates Red if reverse polarity is detected.

**Manual Override.** Is a special feature designed for rare situations when a vehicle's battery is below 2-volts. Simply press and hold the manual overide button for 3 seconds, until the Boost LED starts flashing, to enter into the mode. Press the button again (Or the power button) to exit Manual Override. This mode should be used cautiously, as Manual Override disables safety protection while enabled.

#### **Technical Specifications**

Internal Battery:	24 Watt-Hour Lithium Ion	Housing Protection:	IP65 (w/ Ports closed)
Peak Current Rating:	1000A	Cooling:	Natural Convection
<b>Operating Temperature:</b>	-4°F to +122°F (-20°C to +50°C)	Dimensions (LxWxH):	6.7 x 3.2 x 1.7 in
Charging Temperature:	32°F to +104°F (0°C to +40°C)	Unit Weight:	1.65 lbs
Storage Temperature:	-4°F to +122°F (-20°C to +50°C)	Unit Weight w/Clamps & Accessories:	2.4 lbs
Micro USB (Input):	5V, 2.1A		
USB (Output):	5V, 2.1A	LED Flashlight Brightness:	100 Lumens

What's In The Box

• User Guide & Warranty Information

FC RoHS

GB40 Lithium Jump Starter

Heavy-Duty Battery Clamps

12V Car Charger

Micro USB CableMicrofiber Storage Bag

Recharge Unit

from any USB or 12V port.

# Recharging a GB40 (for reference, results may vary) USB Charger Rating Charging Time .5A 12hr 1A 6hr 2A 3hr Retail Packaging: Master Carton: Dimensions: 3.62°x4.57°x8.27" Dimensions: 9.25°x12.60°x11.

Weight: 2.75lbs UPC: 0-46221-15002-5

Inner Carton: Dimensions: 4.01"x8.78"x5.12" Weight: 2.89lbs


30339 Diamond Parkway, #102

Glenwillow, OH 44139 | USA 1.800.456.6626

NOCO

Master Carton: Dimensions: 9.25"x12.60"x11.22" Weight: 18.30lbs Quantity: 6 UCC: 10046221150022

no.co

Units Per Pallet: NA - 360 Units FU - 270 Units 



1.7in

(43.4mm)

3.2in

(80.3mm)

Base cc Base cc Base and the second s

**NOCO**<sup>°</sup> Patented Technology

Patented: visit no.co/p